

T1545T

KEY CAPABILITIES EXCELLENT VALUE

From breaking even the most stubborn beads to quickly and easily mounting a wide variety of tire sizes and styles, the John Bean® T1545T has the features you need to get the job done right.

The on-floor bead breaker is operated by an ergonomically located pedal placed behind a guard to prevent accidental operation.

The patented two-cylinder system easily grips a wide variety of wheel sizes with self-centering, nylon-covered clamps.

To reduce the risk of overinflation, an integrated pressure monitoring system ensures that tires do not exceed 55 PSI, while PROspeed™ provides optimized torque and RPM during the mounting process.

The John Bean T1545T helps you keep tire business where it belongs - right in your shop.



SWING-ARM TIRE CHANGER



SWING-ARM

The mounting arm swings to the side so that the machine can be installed in a space-saving way directly near a wall.



PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.



ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.



PNEUMATIC BEAD ASSIST

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tires.

*Optional feature for T1545T

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.

JohnBean®

T1545T



ADJUSTABLE CLAMPING JAWS

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

COLUMN-INTEGRATED AIR TANK

Unobtrusive, vertical design, column-integrated air tank helps conserve valuable shop space with a large volume for increased blasting capabilities.

TABLETOP BEAD SEATER

A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.

Shown with optional Pneumatic Bead Assist.

TECHNICAL SPECIFICATIONS

Max Rim Diameter	24" 61cm
Max Tire Width	15" 38cm
Max Wheel Diameter	50" 127cm
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	82"x49"x52" 208x124x132cm

STANDARD ACCESSORIES

- Wave Plus Tire Lever
- Plastic Rim Protector
- Bead Breaker Blade Protector
- Lube Bucket
- Lube Brush
- Protective Insert for Mount/Demount Head



Applies only to Canadian models:
This product conforms to UL STD 201
and is Certified to CSA STD C22.2 #68



UNITED STATES
800.362.4618

CANADA
800.362.4608



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tire shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2023 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswH22029b (NA en) 02/2023

