# **15K 4-POST PREMIUM FEATURES EFFICIENT SERVICE** Efficiently work on more vehicle types with the John Bean® 15k Four-Post Lift. Are you looking to work on a variety of vehicles at your shop? The John Bean 15k Four-Post Lift can handle everything from dual-wheel, heavy-duty trucks to compact sedans and SUVs. This incredibly durable lift has features like an ultra-wide column clearance, 26-inch pro-style runways, open-front cross beam, and enhanced rear slip plates to optimize the task of aligning a wide variety of vehicle Certified by ALI to meet the most stringent

# **FOUR-POST**ALIGNMENT LIFT

ANSI requirements, this is a lift that will provide years of durable, fault-free operation

Increase revenue and customer base with the John Bean 15k Four-Post Alignment Lift.

to your shop.



#### **OPEN-FRONT CROSS BEAM**

Easily access service areas and enjoy optional lighting kits that make performing adjustments quick and efficient. Versatile front wheel stops are specially designed to meet ALI requirements and accommodate ultra-low profile, long vehicles.



#### **WIDER REAR COLUMN CLEARANCE**

Enjoy the convenience of wider rear columns with a full 120 inches of drive-on clearance and 125 inches of body clearance. The John Bean 15k Four-Post lift allows heavy-duty, dual-wheel trucks to drive on with ease.



#### **LOW-PROFILE ROLLING JACKS**

This low-profile jack can collapse and retract inside the runways, has a half-inch diameter roller shaft, and high-quality springs to allow the jack to settle on the rail.



Be FAS

#### **PRO-STYLE RUNWAYS**

The John Bean 15k Four-Post utilizes a best-in-class 26-inch wide runway to easily accommodate wide-track vehicles. Low-profile vehicles won't present a problem with an "easy-on" ramp and 8-inch lowered height.



# **15K 4-POST**



# **TECHNICAL SPECIFICATIONS**

Lifting Capacity	15,000 lbs.   6,804 kg
Configuration	Open Front
Overall Width	142"   361cm
Overall Height	Standard: 99"   251cm
Max Lifting Height	78"   198cm
Lifting Time	85 seconds
Power Requirements	208-230V 60Hz 1Ph 30A 3HP   2.2kW
Air Supply Required	90-120 PSI   6-8 BAR

# STANDARD ACCESSORIES

- · Approach Ramp Kit
- 2 Rolling Jack Beams w/Stack Pads
- Premium Turnplates
- Rollback Paddle Kit
- Work Step

### **OPTIONAL ACCESSORIES**

- 52-inch Extended Ramp Option
- Drive-Through Kit
- Turnplate Pocket Cover
- 3 Phase Power Unit





