



# RECOMMENDED EQUIPMENT

---

FOR **HYUNDAI** WORKSHOPS

**John Bean**

**WHEEL ALIGNERS**

P. 02

**V3400****V3300****V2380****V2100****WHEEL BALANCERS**

P. 06

**B2000P****B200S****TIRE CHANGERS**

P. 08

**T7800****T7700****T7100S****SYSTEM V****SYSTEM IV-E****SYSTEM III-E****SYSTEM II-E****LIFTS**

P. 15

**12K SCISSOR****12K TWO-POST****10K TWO-POST**

# \*V3400

## WIRELESS DRIVE-THROUGH WHEEL ALIGNMENT SYSTEM

If you're looking for the ultimate in precision with a high degree of mobility and installation flexibility, look no further than the John Bean® V3400 wheel alignment machine.

The V3400 utilizes a drive-through design with fully wireless Bluetooth® connected camera towers for easy installation in various bay types, especially when paired with the optional mobility kit.

Automatic camera tracking eliminates the need to readjust the camera after raising the lift, while a continuously calibrating third camera retains ultimate accuracy. Touchless AC400 clamps accommodate a full range of tire sizes and ensure a safe, damage-free attachment without touching the rim while applying limited clamping force. Each step in the alignment procedure has been carefully designed to provide the ultimate precision for every adjustment. Our advanced software features enable technicians to perform specialized vehicle measurements such as scrub radius, caster trail, pro-Ackerman, and more, making the V3400 ideal for top-tier precision and convenience in wheel alignment.



\* U.S. OEM only

## KEY FEATURES

### Drive-Through Design

The dual-tower design can accommodate larger-width vehicles by allowing the technician to position the towers apart at optimal distances. This also leaves space at the front of the vehicle to perform other tasks such as ADAS recalibration.

### Mobility Kit

The optional mobility kit allows for easy relocation of the XD camera alignment towers within the shop, giving the ability to move between bays or out of the way, as needed.

### OEM Procedures

The software provides the recommended procedures defined by the manufacturer and indicates the correct clamps for an accurate OEM-specified wheel alignment.

### Automatic Camera Tracking

Cameras move automatically up and down following the targets, eliminating manual adjustments of the camera beam.

## TECHNICAL SPECIFICATIONS

<b>Tire Diameter (AC400)</b>	19"-39"   48-99cm
<b>Wheel Diameter (AC200)</b>	12"-24"   30-61cm
<b>Track Width</b>	48"-96"   122-244cm
<b>Wheelbase</b>	79"-180"   201-457cm
<b>Power Supply</b>	110-240V 50/60Hz

# \*V3300

## WORRY-FREE DIAGNOSTIC WHEEL ALIGNMENT SYSTEM

Work faster and smarter with the John Bean® V3300 Diagnostic Wheel Aligner.

The V3300 is a stand-alone wheel alignment system that utilizes advanced technology to guide technicians of all skill levels through the wheel alignment process. We've combined the fastest camera system ever offered by John Bean with advanced notification alerts and clever software flow to reduce alignment errors, as well as decrease overall alignment time. This means you can push more alignments through with fewer errors; drastically increasing your productivity and boosting your revenue. The V3300 is the ultimate in wheel-alignment technology.



\* U.S. OEM only

## KEY FEATURES

### Avoid Errors

The advanced notification system on the V3300 instantly recognizes any error made during the alignment process and allows technicians to instantly correct the error during the alignment operation procedure. From suspension stress to uneven rack surfaces and loose components; the V3300 eliminates alignment errors and speeds up the entire alignment process.

### Real-Time Support

Looking for real-time support? The V3300 goes beyond wheel alignment to offer critical, real-time data from OEM's such as repair information, TSBs, recalls, and TPMS reset procedures. This means less time searching for resources to get the job done right and more time pushing alignments through your shop.

### ADAS Integration

ADAS calibration is a consistent reality for modern shops that perform alignment procedures on their customer's vehicles. Performing ADAS calibration accurately can be a constant source of productivity issues due to the sheer variety of procedures and the ever-changing OEM calibration requirements. The V3300 makes this task easy with real-time information on vehicle-specific ADAS procedures. Combine the V3300 with the John Bean Tru-Point™ recalibration system for ultimate productivity.

### Fast Compensation and Optimized Alignment Flow

Streamline workflow with fast measurement compensation and an optimized alignment flow that enhances productivity by eliminating unnecessary steps in the alignment process.

## TECHNICAL SPECIFICATIONS

<b>Tire Diameter (AC400)</b>	19"-39"   48-99cm
<b>Wheel Diameter (AC200)</b>	12"-24"   30-61cm
<b>Track Width</b>	48"-96"   122-244cm
<b>Wheelbase</b>	79"-180"   201-457cm
<b>Power Supply</b>	110-240V 50/60Hz

# \*V2380

## IMAGING DIAGNOSTIC WHEEL ALIGNMENT SYSTEM

The John Bean® V2380 wheel aligner combines a classic post and beam design with the ultimate productivity-boosting technology to give shop owners the edge they need to perform efficient wheel alignment services.

If your shop is looking to perform accurate alignment services at a fast pace, the John Bean V2380 is designed to get the job done with fast compensation and optimized alignment flow. Work quickly and accurately without slowing down critical alignment procedures by using our advanced notification system that instantly alerts the technician of suspension stress issues or other errors. Smart features like fast compensation and instant error notifications allow technicians to quickly move through optimized alignment steps. If technicians hit a snag while performing alignment services, Mitchell1® on-demand gives access to an extensive online, real-time database to work through nearly any alignment problem. Productivity boosting features like automatic camera tracking, EZ-Toe, and our exclusive AC400 wheel clamps help you drive more alignments through your shop.

\* U.S. OEM only



## KEY FEATURES

### Fast Compensation and Optimized Alignment Flow

Streamline workflow with fast measurement compensation and an optimized alignment flow that enhances productivity by eliminating unnecessary steps in the alignment process.

### Advanced Notification System

The advanced notification system provides critical information without slowing down the alignment process, automatically detecting and compensating suspension stress issues or environmental errors, only notifying the technician when necessary to provide additional information for corrective action.

### Audit Mode

Quickly uncover extra service opportunities with alignment audit reports. This report includes measurement of track width, front and rear toe, camber, wheelbase, wheel diameter, and cross dimensions.

### Auto Camera Tracking

Automatic camera tracking eliminates the need to readjust the camera after raising the lift, while a continuously calibrating third camera retains ultimate accuracy.

## TECHNICAL SPECIFICATIONS

<b>Tire Diameter (AC400)</b>	19"-39"   48-99cm
<b>Wheel Diameter (AC200)</b>	12"-24"   30-61cm
<b>Track Width</b>	48"-96"   122-244cm
<b>Wheelbase</b>	79"-180"   201-457cm
<b>Power Supply</b>	110-240V 50/60Hz

# \*V2100

## TILT BEAM IMAGING WHEEL ALIGNMENT SYSTEM

Small in size but not in features, the John Bean® V2100 offers a host of productivity-focused features with a minimal footprint and easy installation options.

It can be challenging to fit an advanced wheel aligner into a shop with a compact footprint, but the John Bean V2100 is up for the task. We've packaged the V2100 to take up minimal room in your shop, with a console-integrated post and beam design. Use your tablet as a wireless secondary display for the ultimate flexibility and ease of use. V2100 can be easily updated via a network connection, ensuring the most up-to-date information is always readily available at your fingertips. Combine these features with our advanced software that includes fast compensation and optimized alignment flow, and you have the ultimate solution for independent shops looking to take advantage of lucrative alignment services.



\* U.S. OEM only

## KEY FEATURES

### Remote Controlled Tilt Beam

A simple remote control allows technicians to tilt the beam quickly and easily.

### Fast Compensation and Optimized Alignment Flow

Enhance productivity and cut down on unnecessary steps with an intelligent, predictive alignment workflow that simplifies the alignment process.

### Advanced Notification System

The advanced notification system provides critical information without slowing down the alignment process, automatically detecting and compensating suspension stress issues or environmental errors, only notifying the technician when necessary to provide additional information for corrective action.

### Small Footprint

Maximize shop floor space with a small console that takes up minimal shop space with easy storage for the printer and targets.

## TECHNICAL SPECIFICATIONS

Wheel Diameter (AC200)	12"-24"   30-61cm
Track Width	48"-96"   122-244cm
Wheelbase	79"-180"   201-457cm
Power Supply	110-240V 50/60Hz



# \*B2000P

## FULLY AUTOMATIC 3D DIAGNOSTIC WHEEL BALANCER

The John Bean® B2000P is a fully automatic diagnostic wheel balancing system that uses five high-resolution cameras to create a complete 3D mapping system of the rim and tire profile.

Our precision 3D runout measurements provide a commercial-grade level of surface measurement that can help technicians pinpoint balancing issues. A unique suite of diagnostic features such as tread depth analysis, tire wear-out prediction, uneven wear diagnosis, and automatic unbalance measurements help technicians identify weight and shape defects, flat spots, and incorrect bead seating. Our easy-to-read, intuitive software interface and touchscreen display provide all the necessary steps for technicians throughout the entire balancing process, boosting productivity and reducing potential operator error.

Not all tires are perfect, which can cause drivability issues such as vibration and pull. Our exclusive OptiLine™ technology analyzes the data of the complete wheelset and proposes the best placement for each wheel to compensate for tire pulling or steering wheel vibration problems. This feature provides accuracy on another level.

The John Bean B2000P is a world-class diagnostic wheel balancing system for professional shops. This technological powerhouse allows technicians to balance a wide variety of wheels with the highest degree of accuracy.

\* U.S. OEM only



## KEY FEATURES

### Runout Measurements

Hundreds of thousands of measurement points are taken with a resolution of 0.004" (0.1 mm) to create a 3D model of the tire and wheel allowing for a complete diagnosis of the assembly uniformity and displaying radial runout with peak-to-peak measurements from the first to the third harmonic.

### Match Mounting

Optimize the assembly of the tire on the rim and reduce the amount of necessary weight.

### Laser 3D Surface Mapping

Utilizes a high-resolution camera and laser-based technology to provide sidewall analysis, as well as depth, wear, and tire surface abnormalities that are displayed in an easy-to-read format.

### OptiLine™ Wheel Set Optimization

Based on a predetermined set of criteria, OptiLine suggests the optimal location for each wheel to address any pull or vibration-related issues.

## TECHNICAL SPECIFICATIONS

Max Wheel Diameter	44"   112cm
Max Wheel Weight	154 lbs.   70 kg
Power Supply	230V 50/60Hz
Dimensions HxWxL	74"x48"x62"   189x123x158cm

# \*B200S

## SEMI-AUTOMATIC WHEEL BALANCER

Designed to fit into a variety of shop sizes with a small footprint, the John Bean® B200S wheel balancer may be small in size but it gets the job done right.

Offering an easy-to-navigate interface and a raised monitor with color display, the B200S helps technicians quickly and accurately balance wheels. Productivity-enhancing features like smartSonar™ and easyALU™ allow users to measure wheels and quickly move through a balancing cycle. The EZ-Collets app gives technicians the assistance they need in finding the right tool for the job.

Small in size with useful features, the John Bean B200S wheel balancer helps you keep profitable wheel service where it belongs: in your shop.



\* U.S. OEM only

## KEY FEATURES

### smartSonar™

Automatic rim width detection using sonar sensors to avoid manual entry errors.

### Quick Nut Wheel Clamp

An easy-to-use manual clamping device that allows a secure attachment of the wheel to the balancer shaft.

### Semi-Automatic Data Entry

Hand-operated gauge arm with easyALU™ assisted rim data entry for diameter and distance. Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.

### Split Weight Mode

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.

## TECHNICAL SPECIFICATIONS

Max Wheel Diameter	42"   107cm
Max Wheel Weight	154 lbs.   70 kg
Power Supply	230V 50/60Hz
Dimensions HxWxL	72"x31"x40"   183x78x101cm



# \*T7800

## LEVERLESS ALL-IN-ONE TIRE CHANGER

Increase productivity and reduce technician fatigue with the T7800 all-in-one tire changing system from the experts at John Bean®.

Technology and productivity intersect on the John Bean T7800 tire changing system. The experts at John Bean have created a machine with advanced features that allow technicians to mount and demount tires at a stunning pace with minimal fatigue and reduced chance of wheel damage. The center post design utilizes our quickLOK™ powerful electromechanical clamping system to effortlessly and automatically clamp the wheel. The Optimum Bead Breaker System makes short work of breaking beads while minimizing potential wheel damage, even on UHP and run-flat tires. We've included helpful tools like a lower bead camera, PROspeed™ technology, and ergonomic features to make your technician's job as easy as possible.



\* U.S. OEM only

## KEY FEATURES

### powerMONT™

Our leverless mounting and demounting tool synchronizes with the dynamic bead breaker location for optimum positioning. Featuring upgraded steel and plastic protection to ensure long-term operation, this innovative system is a perfect tool for RFT, UHP, OEM's and low-aspect-ratio tires.

### quickLOK™

A powerful, electromechanical device that firmly clamps onto a variety of wheels without the need for wheel protection.

### PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.

### Optimum Bead Breaker System

Bead-breaking tools for the most optimized solution:

**Dynamic Bead Breaker:** The precisely controlled synchronized dual-disk system accurately positions both the upper and lower beads while minimizing the chance of wheel damage. Includes an adjustable tilt for tires with stiff sidewall.

**On-Floor Bead Breaker:** Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.

## TECHNICAL SPECIFICATIONS

<b>Max Rim Diameter</b>	30"   76cm
<b>Max Tire Width</b>	15"   38cm
<b>Max Wheel Diameter</b>	47"   119cm
<b>Wheel Lift Capability</b>	154 lbs.   70 kg

<b>Power Supply</b>	230V 1ph 50-60Hz 16A
<b>Air Pressure Required</b>	116-174 PSI   8-12 bar
<b>Dimensions HxWxD</b>	75"x63"x78"   190x160x198cm

# \*T7700

## LEVERLESS TIRE CHANGER

Maximize shop productivity and work on a wide range of specialty, run-flat, low-profile, and high-performance tires with the John Bean® T7700 tire changer.

Changing tires on modern vehicles that utilize low-profile or run-flat tires can be a challenge for shops that are not properly equipped, due to the potential for wheel damage. The John Bean T7700 leverless tire changer provides a comprehensive set of tools that make changing a wide variety of tires quick and easy while minimizing the chance of wheel damage. Easily move tires into position with a pedal-operated wheel lift and secure the wheel with an innovative center post clamp that can accommodate a wide variety of wheels and tires. The Dynamic Bead Breaker system utilizes two synchronized disks that adjust with pneumatic precision to practically eliminate wheel damage and make short work of removing ultra-high-performance and run-flat tires. Our powerMONT™ tool makes mounting and demounting tires a snap. For high-volume and specialty shops, this is the ultimate productivity workhorse.

\* U.S. OEM only



## KEY FEATURES

### powerMONT™

Our leverless mounting and demounting tool synchronizes with the dynamic bead breaker location for optimum positioning. Featuring upgraded steel and plastic protection to ensure long-term operation, this innovative system is a perfect tool for RFT, UHP, OEM's and low-aspect-ratio tires.

### PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.

### Dynamic Bead Breaker

The precisely controlled synchronized dual-disk system accurately positions both the upper and lower beads while minimizing the chance of wheel damage. Includes an adjustable tilt for tires with stiff sidewall.

### Control Panel

The color-coded control panel is simple to use with tool-matching operation controls.

## TECHNICAL SPECIFICATIONS

<b>Max Rim Diameter</b>	30"   76cm
<b>Max Tire Width</b>	15"   38cm
<b>Max Wheel Diameter</b>	47"   119cm
<b>Wheel Lift Capability</b>	154 lbs.   70 kg

<b>Power Supply</b>	230V 1ph 50-60Hz 16A
<b>Air Pressure Required</b>	116-174 PSI   8-12 bar
<b>Dimensions HxWxD</b>	75"x63"x78"   190x160x198cm

# \*T7100S

## CENTER POST SWING-ARM TIRE CHANGER

We've combined classic design with modern features to make it easy for technicians of all levels to quickly and safely change tires with the John Bean® T7100S tire changer.

Utilizing a traditional swing-arm style with a center post clamp design, the John Bean T7100S offers speed and precision for efficient tire changing operation. The on-floor hand-activated bead breaker shovel makes quick work of the toughest tires, while an integrated wheel lift helps reduce technician fatigue and increase productivity. The center post clamp with anti-rotational pin accommodates a wide range of wheel sizes and minimizes the chance of wheel damage, and the pneumatic bead assist enables efficient single-operator mounting and demounting of the upper bead. Our patented PROspeed™ technology monitors torque and optimizes the rotation speed to minimize the chance for tire damage throughout the operation.

For high-volume shops that need a tire changer with optimum technology, the T7100S is the machine for the job.



\* U.S. OEM only

## KEY FEATURES

### Center Post Clamp

The center-post clamp design has numerous benefits, most important is the drastically reduced risk of wheel damage and less clamping restriction than the turntable design.

### PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.

### Pneumatic Wheel Lift

The pedal-operated pneumatic wheel lift assists in lifting heavy wheels to reduce technician fatigue and increase productivity.

### On-Floor Bead Breaker (Hand-Controlled)

Pneumatic assist control handle prevents shovel bounce-back with this on-floor bead breaker; the fastest solution for standard, soft sidewall, and high-aspect tires.

## TECHNICAL SPECIFICATIONS

<b>Max Rim Diameter</b>	30"   76cm
<b>Max Tire Width</b>	15"   38cm
<b>Max Wheel Diameter</b>	44"   112cm
<b>Wheel Lift Capability</b>	154 lbs.   70 kg

<b>Power Supply</b>	230V 1ph 50-60Hz 16A
<b>Air Pressure Required</b>	116-174 PSI   8-12 bar
<b>Dimensions HxWxD</b>	64"x62"x63"   163x157x160cm

# \*SYSTEM V

## TILT-TOWER TIRE CHANGER

Traditional tilt-tower design meets productivity-boosting and damage avoidance features to make the John Bean® System V a solid addition to smaller, independent shops that service a variety of wheel and tire combos.

For high-volume shops that service OEM cars, SUV's, and light to medium truck applications, the System V is a great addition to your workflow. An on-floor bead breaker with an ergonomically located pedal makes breaking even the toughest beads easy and safe. The pneumatically locking tilt-tower configuration easily moves out of the way to ergonomically allow placement of small to large wheels. Once the tire is on the turntable, the self-adjusting four-jaw clamp secures the wheel clamps with power from twin cylinders. Comprehensive pneumatic bead assist comes standard and provides an additional suite of features that make changing ultra-high performance and run-flat tires a snap. Traditional design, with modern productivity-boosting features, makes the System V a great addition to your shop.



\* U.S. OEM only

## KEY FEATURES

### Tilt-Tower

The pneumatic Tilt-Tower post provides maximum clearance for installing the tire on the turntable.

### On-Floor Bead Breaker (Pedal-Operated)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.

### Pneumatic Bead Assist

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tires.

### Adjustable Clamping Jaws

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

## TECHNICAL SPECIFICATIONS

Max Rim Diameter	26"   66cm
Max Tire Width	17"   43cm
Max Wheel Diameter	47"   119cm
Wheel Lift Capability	154 lbs.   70 kg

Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	58"x65"x90"   147x165x229cm

# \*SYSTEM IV-E

## TILT-TOWER TIRE CHANGER

For medium to high-volume shops interested in keeping revenue-boosting tire services in-house while keeping to a strict budget and looking to service OEM cars, SUV's and light trucks; the John Bean® System IV-E includes several productivity-boosting features without the high price tag.

The System IV-E traditional tilt-tower design combined with a handy two-speed turntable and a bevy of productivity-boosting features allows you to keep revenue-boosting tire services where they belong - in your shop. An on-floor bead breaker with an ergonomically located pedal makes breaking even the toughest beads easy and safe. The pneumatic locking tilt-tower configuration easily moves out of the way to ergonomically allow placement of small to large wheels. Once the tire is on the turntable, the self-adjusting four-jaw clamp secures the wheel with twin-cylinder clamping power, and the integrated tire pressure limiter eliminates the possibility of over-inflation. Big features, smaller price; the System IV-E is a great addition to any medium to high-volume shop.

\* U.S. OEM only



## KEY FEATURES

### Tilt-Tower

The pneumatic Tilt-Tower post provides maximum clearance for installing the tire on the turntable.

### On-Floor Bead Breaker (Pedal-Operated)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.

### Pneumatic Bead Assist

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tires.

### Adjustable Clamping Jaws

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

## TECHNICAL SPECIFICATIONS

Max Rim Diameter	24"   61cm
Max Tire Width	13"   33cm
Max Wheel Diameter	39"   99cm
Wheel Lift Capability	154 lbs.   70 kg

Power Supply	115V 1ph 60Hz 12A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	79"x61"x56"   201x155x142cm

# \*SYSTEM III-E

## SWING-ARM TIRE CHANGER

Looking to keep high-revenue tire business in house? Work faster without compromising safety or wheel protection with the John Bean® System III-E swing-arm tire changer.

If you regularly work on larger wheels and tires that are common on today's modern performance cars and SUVs, the John Bean System III-E swing-arm tire changer is a fantastic addition to your shop. The System III-E allows you to work on tires up to 15 inches in width and 42 inches in diameter, which covers a range of vehicles. An ergonomic, pedal-operated on-floor bead breaker allows technicians to work with tires all the way up to 15 inches wide with ease. Powered by twin cylinders, the nylon-covered clamping jaws make quick work of holding large wheels in place on the turntable while minimizing the chance of damage. Big features packed in a compact footprint - the System III-E is the workhorse you need.



\* U.S. OEM only

## KEY FEATURES

### Swing-Arm

The mounting arm swings to the side so that the machine can be installed in a space-saving way directly near a wall.

### On-Floor Bead Breaker (Pedal-Operated)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.

### Pneumatic Bead Assist

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tires.

### Adjustable Clamping Jaws

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

## TECHNICAL SPECIFICATIONS

<b>Max Rim Diameter</b>	24"   61cm
<b>Max Tire Width</b>	15"   38cm
<b>Max Wheel Diameter</b>	50"   127cm
<b>Wheel Lift Capability</b>	154 lbs.   70 kg

<b>Power Supply</b>	115V 1ph 60Hz 12A
<b>Air Pressure Required</b>	116-174 PSI   8-12 bar
<b>Dimensions HxWxD</b>	82"x49"x52"   208x124x132cm



# \*SYSTEM II-E

## SWING-ARM TIRE CHANGER

Keep high-revenue tire business in-house and work faster without compromising safety or wheel protection by adding the John Bean® System II-E swing-arm tire changer to your shop.

Today's modern cars, trucks, and SUVs come with a wide variety of hard-to-service wheel and tire combos, but the John Bean System II-E swing-arm tire changer is up to the task. The System II-E allows you to work on a wide range of tires, up to 12 inches in width and 40 inches in diameter. An ergonomic pedal-operated on-floor bead breaker allows technicians to work with tires all the way up to 13 inches with ease. Powered by twin cylinders, nylon-covered clamping jaws make quick work of holding large wheels in place on the turntable while minimizing the chance of damage. Big features, packed in a shop-friendly footprint - the System II-E is the workhorse you need.



\* U.S. OEM only

## KEY FEATURES

### Swing-Arm

The mounting arm swings to the side so that the machine can be installed in a space-saving way directly near a wall.

### Adjustable Clamping Jaws

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

### On-Floor Bead Breaker (Pedal-Operated)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.

### Column-Integrated Air Tank

Unobtrusive, vertical design, column-integrated air tank helps conserve valuable shop space with a large volume for increased blasting capabilities.

## TECHNICAL SPECIFICATIONS

<b>Max Rim Diameter</b>	24"   61cm
<b>Max Tire Width</b>	13"   33cm
<b>Max Wheel Diameter</b>	39"   99cm
<b>Wheel Lift Capability</b>	154 lbs.   70 kg

<b>Power Supply</b>	115V 1ph 60Hz 12A
<b>Air Pressure Required</b>	116-174 PSI   8-12 bar
<b>Dimensions HxWxD</b>	71"x45"x55"   180x114x140cm

# \*12K SCISSOR

## SCISSOR ALIGNMENT LIFT

Built for shops that perform alignments day in and day out, the John Bean® 12k Scissor Lift offers durable construction with an open-front design for easy access to alignment service and calibration areas.

The John Bean 12k Scissor Lift is ready to meet the needs of shops that regularly perform alignment services. The lifting capacity can hoist up to 12,000 pounds with power from four heavy-duty cylinders, while the extra-wide 24-inch runways can easily accommodate larger vehicles. Hydraulic equalization and full-support integrated rear synchronization bar deliver repeatable smooth level lifting. Flush-mounted rear slip plates include heavy-duty encapsulated bearings to ease rear alignment adjustments. The approach ramps can be extended up to 87-inches for loading lower-profile vehicles and retract to 35 inches when not in use.

For alignment professionals who need power and productivity, the John Bean 12k Scissor Lift is the ideal tool for the job.



\* U.S. OEM only

## KEY FEATURES

### Retractable Ramps

Approach ramps expand to 87 inches to accommodate low-profile vehicles and retract to 35 inches to save space when not in use.

### Drive-Through Option

Equip your lift with an extra set of ramps that allow vehicles to exit from the front without resorting to backing up.

### Flush or Surface Mount

Maximize your available workspace with a flush-mount installation that can recess right into your shop floor when not in use.

### Integrated Rear Synchronization Bar

A robust, heavy-duty steel bar supports stable up and down movement during operation.

## TECHNICAL SPECIFICATIONS

<b>Lifting Capacity</b>	12,000 lbs.   5,443 kg
<b>Configuration</b>	Open Front
<b>Overall Width</b>	90"   229cm
<b>Overall Height</b>	70"   178cm

<b>Max Lifting Height</b>	70"   178cm
<b>Lifting Time</b>	95 seconds
<b>Power Requirements</b>	2HP 230V 1Ph 60 Hz 20A
<b>Air Supply Required</b>	90-140 PSI @ 5-10 CFM

# \*12K 2-POST

## TWO-POST AUTOMOTIVE LIFT

For shops that work on various cars and trucks, looking for the ultimate power and precision in a superior two-post design, the John Bean® 12k Two-Post Lift will get the job done.

Ready to handle loads of 12,000 pounds, the John Bean 12k Two-Post lift can work on a wide variety of light and medium-duty applications for today's modern shop. Heavy-duty front and rear arms work with a standard set of screw pads and adapters to lift most vehicles in mere seconds. Rubber door guards on the columns prevent accidental vehicle damage. Quickly and safely disengage both columns simultaneously with an easy-to-use, Bowden cable release. We've designed a padded overhead bar that instantly stops the lift, protecting the vehicle from unintentional damage. The John Bean 12k Two-Post is a lift for those that get it done, day in and day out.



\* U.S. OEM only

## KEY FEATURES

### Two-Stage Front & Rear Arms

Heavy-duty two-stage front and rear arms enable a wide range of symmetric lifting.

### Adjustable Height Extension

Increase your service capability to work on taller vehicles, including the largest trucks, SUVs, and cargo vans, with our two-foot column height extension.

### Adjustable Urethane Screw Pads

Heavy-duty polyurethane pad provides ample surface area to the vehicle frame and the telescoping feature provides simple access to factory-recommended lift points.

### Increased Capacity for Larger Vehicles

Work on everything from a mini car to an RV with our high-capacity lift products for maximum revenue potential.

## TECHNICAL SPECIFICATIONS

<b>Lifting Capacity</b>	12,000 lbs.   5,443 kg
<b>Configuration</b>	Symmetric
<b>Overall Width</b>	140"   356cm
<b>Overall Height</b>	Standard: 166"-175"   421-445cm Extended: 190"-199"   483-505cm

<b>Max Lifting Height</b>	78"   198cm
<b>Lifting Time</b>	61 seconds
<b>Power Requirements</b>	2HP 208-230V 60 Hz 1Ph 30A
<b>Air Supply Required</b>	90-120 PSI   6-8 BAR

# \*10K 2-POST

## TWO-POST AUTOMOTIVE LIFT

Packed with premium features without the premium cost, the John Bean® 10k Two-Post Lift is a perfect addition to high-volume shops that work on various light and medium-duty vehicles.

Built to get the job done, the John Bean 10k Two-Post Lift easily handles loads up to 10,000 pounds. For ultimate flexibility, symmetric or asymmetric lifting is possible, and installation of the power unit can be on either side, while the installed height is adjustable by up to 10 inches. Double telescopic lifting pads with replaceable plastic inserts work with three-stage front arms to safely lift a wide variety of vehicle types. Quickly and safely disengage both columns simultaneously with an easy-to-use, single-point Bowden cable release. We've designed a padded overhead bar that instantly stops the lift, protecting the vehicle from unintentional damage.

The 10k Two-Post Lift is the workhorse your shop needs to get the job done efficiently and safely.



\* U.S. OEM only

## KEY FEATURES

### Three-Stage Asymmetric Front Arms & Two-Stage Rear Arms

Confidently and accurately lift vehicles with our easy-to-use three-stage, asymmetric front arms, designed for ease of use and load balancing; two-stage rear arms easily connect to the rear vehicle lifting points.

### Adjustable Height Extension

Increase your service capability to work on taller vehicles, including the largest trucks, SUVs, and cargo vans, with our two-foot column height extension.

### Adjustable Urethane Screw Pads

Heavy-duty polyurethane pad provides ample surface area to the vehicle frame and the telescoping feature provides simple access to factory-recommended lift points.

### Fast Rise Time

Spend less time lifting vehicles and get to work faster with industry-leading rise times.

## TECHNICAL SPECIFICATIONS

<b>Lifting Capacity</b>	10,000 lbs.   4,536 kg
<b>Configuration</b>	Asymmetric
<b>Overall Width</b>	132"   335cm
<b>Overall Height</b>	Standard: 138"-148"   351-376cm Extended: 162"-172"   411-437cm

<b>Max Lifting Height</b>	78"   198cm
<b>Lifting Time</b>	40 seconds
<b>Power Requirements</b>	2HP 230V 1Ph 60 Hz
<b>Air Supply Required</b>	90-120 PSI   6-8 BAR



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tire shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2022 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. ssoe22067 (NA\_en) 07/2022

