

# T1545T

## KEY CAPABILITIES EXCELLENT VALUE

From breaking even the most stubborn beads to quickly and easily mounting a wide variety of tire sizes and styles, the John Bean® T1545T has the features you need to get the job done right.

The on-floor bead breaker is operated by an ergonomically located pedal placed behind a guard to prevent accidental operation.

The patented two-cylinder system easily grips a wide variety of wheel sizes with self-centering, nylon-covered clamps.

To reduce the risk of overinflation, an integrated pressure monitoring system ensures that tires do not exceed 55 PSI, while PROspeed™ provides optimized torque and RPM during the mounting process.

The John Bean T1545T helps you keep tire business where it belongs - right in your shop.

**Be EQUIPT**



## SWING-ARM TIRE CHANGER



### SWING-ARM

The mounting arm swings to the side so that the machine can be installed in a space-saving way directly near a wall.



### PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.



### ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.



### PNEUMATIC BEAD ASSIST (OPTIONAL)

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tires.

**WHEN GOOD ENOUGH ISN'T ENOUGH, JB.**

**JohnBean**

# T1545T

## ADJUSTABLE CLAMPING JAWS

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

## COLUMN-INTEGRATED AIR TANK

Unobtrusive, vertical design, column-integrated air tank helps conserve valuable shop space with a large volume for increased blasting capabilities.

## TABLETOP BEAD SEATER

A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.

Shown with optional Pneumatic Bead Assist.

## TECHNICAL SPECIFICATIONS

|                       |                             |
|-----------------------|-----------------------------|
| Max Rim Diameter      | 24"   61cm                  |
| Max Tire Width        | 15"   38cm                  |
| Max Wheel Diameter    | 50"   127cm                 |
| Power Supply          | 230V 1ph 50-60Hz 16A        |
| Air Pressure Required | 116-174 PSI   8-12 bar      |
| Dimensions HxWxD      | 82"x49"x52"   208x124x132cm |

## STANDARD ACCESSORIES

- Wave Plus Tire Lever
- Plastic Rim Protector
- Bead Breaker Blade Protector
- Lube Bucket
- Lube Brush
- Protective Insert for Mount/Demount Head

## OPTIONAL ACCESSORIES

- Pneumatic Bead Assist



Applies only to Canadian models:  
This product conforms to UL STD 201  
and is Certified to CSA STD C22.2 #68



UNITED STATES  
800.225.5786

CANADA  
800.225.5786



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tire shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2026 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswH22029c (NA en) 09/2026

