

T5325B 2S

CORE FEATURES PROFESSIONAL SERVICE

Built to get the job done, the John Bean® T5325B 2S combines all the helpful features you need to change tyres the right way.

Practical and simple to use, the T5325B 2S offers a tilt-tower design that provides ample clearance to load tyres onto the turntable. The T5325B 2S is equipped with PROspeed™ technology to automatically monitor torque and maintain optimum rotational speed while ensuring the safety of the tyre. Ergonomic and effective, the pedal-operated on-floor bead breaker makes quick work of traditional and high-aspect tyres. Pneumatic bead assist utilises a three-piece design that allows a single technician the ability to mount and demount challenging low-profile tyres. Simple to operate, yet highly effective, the top-side bead seater utilises compressed air to seal the tyre to the rim.

The T5325B 2S provides all the advanced features you need for your tyre changing service.



TILT-TOWER TYRE CHANGER



TILT-TOWER

The pneumatic Tilt-Tower post provides maximum clearance for installing the tyre on the turntable.



PROSPEED™

The innovative self-adjusting technology provides the optimum torque and maximises the rotation speed for safe, efficient operation.



ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres.



TOP-SIDE BEAD SEATER

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.

JohnBean

T5325B 2S



PNEUMATIC BEAD ASSIST

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tyres.

TECHNICAL SPECIFICATIONS

Max Rim Diameter	24" 61cm
Max Tyre Width	13" 33cm
Max Wheel Diameter	39" 100cm
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	63"x73"x70" 160x185X178cm

STANDARD ACCESSORIES

- 5 kg Lube Bucket Holder
- Lube Brush
- Bead Lever Plus
- Bead Lever Protector Plus
- Plastic Rim Protector: Clip-on Type
- Bead Breaker Blade Sleeve
- Alloy Rim Protector Kit for Centre Type Sliding Jaws - Front & Rear

OPTIONAL ACCESSORIES

- Plastic Tyre Protector: Clip-on Type
- Smart Bead Spacer Tail
- Bead Clamp
- Bead Press Tool MX
- Bead Pressing Roller for M/D Tool
- Quick Exchange Device with Mounting Head
- Wheel Lift

FIND A DISTRIBUTOR



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers, and tyre shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2025 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. ssw22279b (EU en) 08/2025

AUSTRIA
+43 2641 24 5 24

FRANCE
+33 134 48 58 78

GERMANY
+49 8671 96200 0

ITALY
+39 0522 733 411

JB
johnbean.com