

FOUR-POST ALIGNMENT LIFT

Keep pace with the changing customer requirements with the John Bean dual revenue 4 post lift and its options for MOT, ATL and wheel alignment work. The lift has three configuration options (MOT/Alignment; ATL/Alignment; Alignment only) and two weight capacity choices (4T; 5T) to provide different solutions depending on requirements

AVAILABLE CONFIGURATIONS

Class IV, 4000KG 4 post car lift with a 5.2m platform length, and is available in the following configurations:

- MOT/Alignment front turning plates and built-in rear slip plates
- ATL/Alignment as per MOT lift above but also includes the SPD 2000 DVSA-approved axle play detector
- Alignment alignment table, similar to MOT lift above, not supplied with turn plates but does have space to fit 470mm precision turning plates

Class VII, 5000KG 4 post car lift with a 5.7m platform length, and is available in the following configurations:

- MOT/Alignment front turning plates and built-in rear slip plates
- ATL/Alignment as per MOT lift above but also includes the SPD 2000 DVSA-approved axle play detector
- · Alignment alignment table, similar to MOT lift above, not supplied with turn plates but does have space to fit 470mm precision turning plates

FEATURES

- · Advanced safety and audible safety alert: The electrical safety locking provides a failsafe system with an audible safety alert on descent
- · Rear slip plates: Integrated rear slip plates with high quality finish platform allowing for dual usage when carrying out wheel alignment
- · Elephant trunking: Elephant trunking is provided as standard to help keep pipes and hoses tidy
- Play detectors (ATL Only): Our play detectors are more likely to find faults than any other on the market as they accentuate any wear in steering components
- Wireless torch/controller (ATL Only): Integral inspection lamp incorporating buttons for play detector operation
- \bullet Optional jacking beam: A jacking beam is also an available option for this model



CLASS VII



TECH SPECS

LIFT	4000kg	5000kg	
Platform Length	5200mm	5700mm	
Overall Width	3310mm	3310mm	
Overall Length (Recessed)	5500mm	6000mm	
Minimum Platform Height	190mm	190mm	
Maximum Platform Height	1830mm	1830mm	
Distance Between Platforms	800mm	800mm	
Slip Plate Length	1980mm	2480mm	
Power Requirements	380v 3P + Earth 20A 50Hz	380v 3P + Earth 20A 50Hz	
Foundation	200mm	200mm	
SPD 2000 PLAY DETECTOR	4000kg	5000kg	
Certified Max Weight	1300kg per Wheel	1300kg per Wheel	
Stroke Per Plate	+/- 40mm	+/- 40mm	
	16 11 11 1 1 1 1 1 1 1		

^{*}Snap-on reserves the right to make changes to specifications without notice and without making changes retroactively.







